

SPHS..EC 系列



Bearing Designation	Dimensions mm													Ball Diameter	Load Rating (KN)		Weight ≈Kg
	d H7	B	C1	d1	d2	d3-6H	h1	L3	(L4)	L5	d4	d5	sw		Dynamic Load	Static load	
SPHS5EC	5	8	6	7.7	16	M5	27	11	35	4	11	9	11.11	13	3.3	6.2	0.016
SPHS6EC	6	9	6.75	8.9	18	M6	30	13	39	5	13	11	12.7	13	4.7	7.8	0.025
SPHS8EC	8	12	9	10.3	22	M8	36	16	47	5	16	14	15.87	14	7.7	13.2	0.043
SPHS10EC	10	14	10.5	12.9	26	M10	43	20	56	6.5	19	17	19.05	13	10.4	17.3	0.072
SPHS12EC	12	16	12	15.4	30	M12	50	23	65	6.5	22	19	22.22	13	13.5	22.7	0.107
SPHS14EC	14	19	13.5	16.8	34	M14	57	27	74	8	25	22	25.4	16	17.2	28.2	0.16
SPHS16EC	16	21	15	19.3	38	M16	64	32	83	8	27	22	28.58	15	21	35.1	0.21
SPHS18EC	18	23	16.5	21.8	42	M18X1.5	71	35	92	10	31	27	31.75	15	25	43.2	0.295
SPHS20EC	20	25	18	24.3	46	M20x1.5	77	39	100	10	34	30	34.92	14	29.8	50.3	0.38
SPHS22EC	22	28	20	25.8	50	M22x1.5	84	42	109	12	37	32	38.1	15	36.2	63.9	0.49